

# Radial OTR



## Dump Truck



### LMS401(E-4)

Radial OTR

- Exceptional traction  
Massive tread blocks characterise this tyre, it delivers excellent tractive performance, better lateral adhesion and more efficient loading for machines working at the face.
- Good self cleaning  
Flower chimb angle changed design, it delivers good self cleaning.
- Operating comfort  
A wide, square tread gives better stability in loading operations and whilst travelling.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
26.5R25	☆☆	193	209	22.00/3.0	11500	450	18500	575	1798	673	56
29.5R25	☆☆	200	216	25.00/3.5	14000	450	22400	575	1921	750	61



### DO993(E-3)

Radial OTR

- 1.Good traction resistance.
- 2.Chip,cut and abrasion resistance tread compound.
- 3.Deep tread depth increases mileage and service life.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
13.00R25	☆☆☆	163	182	8.50	4875	700	8500	950	1300	350	30.0
14.00R24	☆☆☆	169	188	10.00	5800	700	10000	950	1370	375	30.0
14.00R25	☆☆☆	169	188	10.00	5800	700	10000	950	1370	375	30.0



## LB02S(E-4)

Radial OTR

- 1. Exceptional traction and manoeuvrability.
- 2. Good flotation.
- 3. Excellent stability and comfort.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
18.00R33	☆☆	191	209	13.00/2.5	10900	650	18500	800	1877	498	53.0



## LB03S(E-4)

Radial OTR

- 1. High safety.
- 2. Wide contact area with ground provides strong grip.
- 3. Low noise.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
16.00R25	☆☆	177	195	11.25/2.0	7300	650	12150	800	1548	432	42.0
18.00R25	☆☆	185	204	13.00/2.5	9250	650	16000	800	1673	498	46.0



## LB06S(E-3)

Radial OTR

- 1. Good traction and wear resistance.
- 2. Excellent tear resistance.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
750/65R25	☆☆	190	--	24.00/3.0	10600	425	--	--	1610	754	45.0
26.5R25	☆☆	193	209	22.00/3.0	11500	450	18500	575	1750	673	44
29.5R25	☆☆	200	216	25.00/3.5	14000	450	22400	575	1873	750	44



## DM992

Radial OTR

- 1. Long life.
- 2. Excellent adhesion and traction in bad conditions.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
13.00R25	☆☆☆	163	182	10.00	4875	700	8500	950	1300	350	26.0
14.00R24	☆☆☆	169	188	10.00	5800	700	10000	950	1370	375	26.0
14.00R25	☆☆☆	169	188	10.00	5800	700	10000	950	1370	375	24.0



## DM992+

Radial OTR

- 1. Long life.
- 2. Excellent adhesion and traction in bad conditions.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
13.00R25	☆☆☆	163	182	10.00	4875	700	8500	950	1300	350	26.0
14.00R24	☆☆☆	169	188	10.00	5800	700	10000	950	1370	375	26.0

# Loader



## LB01N(E-3/L-3)

Radial OTR

- 1. Exceptional traction and manoeuvrability.
- 2. Good flotation.
- 3. Excellent stability and comfort.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
17.5R25	☆☆	167	182	14.00/1.5	5450	450	8500	575	1348	445	27.0
20.5R25	☆☆	177	193	17.00/2.0	7300	450	11500	575	1492	520	30.0
23.5R25	☆☆	185	201	19.5/2.5	9250	450	14500	575	1617	597	33.0
26.5R25	☆☆	193	209	22.00/3.0	11500	450	18500	575	1750	673	36.0
29.5R25	☆☆	200	216	25.00/3.5	14000	450	22400	575	1873	750	39.0



## LM01N(E-3/L-3)

Radial OTR

- 1. Exceptional traction and manoeuvrability.
- 2. Good flotation.
- 3. Excellent stability and comfort.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
23.5R25	☆☆	185	201	19.5/2.5	9250	450	14500	575	1617	597	30.5



## LB03SD(L-5)

Radial OTR

- Exceptionally robust in masacre conditions
- A substantial crown, robust shoulders reinforced with a protection band make up a tyre particularly resistant to shock ruptures, cuts and tread tearing.
- A particularly resilient casing with the addition of several specific steel belts constitute a tyre that is very resistant to punctures.
- Excellent compromise of adhesion and traction
- A very substantial, wide and aggressive tread functions perfectly to produce a good compromise between adhesion, traction and damage resistance.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
17.5R25	☆☆	167	182	14.00/1.5	5450	450	8500	575	1399	445	64
20.5R25	☆☆	177	193	17.00/2.0	7300	450	11500	575	1548	520	71
23.5R25	☆☆	185	201	19.5/2.5	9250	450	14500	575	1673	597	77.5
26.5R25	☆☆	193	209	22.00/3.0	11500	450	18500	575	1798	673	86.5
29.5R25	☆☆	200	216	25.00/3.5	14000	450	22400	575	1921	750	94



## LB02SD(L-5)

Radial OTR

- Exceptional traction
- Massive tread blocks characterise this tyre.
- High Efficiency
- The extra deep tread pattern (L5) of this tyre gives outstanding wear life potential.
- The sidewall/tread intersection design gives an excellent level of damage and cut resistance.
- Operating comfort
- A wide, square tread gives better stability in loading operations and whilst travelling.
- A directional pattern.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
20.5R25	☆☆	177	193	17.00/2.0	7300	450	11500	575	1548	520	71
23.5R25	☆☆	185	201	19.5/2.5	9250	450	14500	575	1673	597	77.5
26.5R25	☆☆	193	209	22.00/3.0	11500	450	18500	575	1798	673	86.5
29.5R25	☆☆	200	216	25.00/3.5	14000	450	22400	575	1921	750	94

# Sand



## LD702(E-7)

Radial OTR

- 1.The combination of vertical and horizontal pattern groove.
- 2.Strengthened bead area and Tubeless solution preventing sudden pressure loss.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)
24R20.5	☆ /16PR	176	F	18.00	7100	600	1370	600	21.0

# Motor Tractor



## LLA28

Radial OTR

- 1.Good traction resistance.
- 2.Chip,cut and abrasion resistance tread compound.

Size	Ply Rating	Load Index		Rim	LOAD CAPACITY(kg)				Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
		TRANSP 50km/h Speed Symbol B	LOADING 10km/h Speed Symbol A2		TRANSPORT		LOADING				
					LOAD 50km/h Speed Symbol B (kg)	Inflated Pressure (kPa)	LOAD 10km/h Speed Symbol A2 (kg)	Inflated Pressure (kPa)			
16.00R25	☆☆	177	195	11.25/2.0	7300	650	12150	800	1493	432	23.0

# Mobile Crane



## LM11N

Radial OTR

- 1.Exceptional traction and manoeuvrability.
- 2.Good flotation.
- 3.Excellent stability and comfort.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Standard Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Overall Width (mm)	Tread Depth (mm)
445/95R25	☆☆	177	E	11.25/2.0	7300	900	1481	435	23.0
385/95R25	☆☆	170	E	10.00/1.5	6000	900	1369	379	21.0



# Bias

## OTR



## Dump Truck



### LL131(E-3)

OTR Tire

1. Available for large rigid dump trucks.
2. Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
13.00-25	28	8.50	--	--	4800	710	335	1300	24.5	TT



### LL42(E-3)

OTR Tire

1. Available for large rigid dump trucks.
2. Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
14.00-24	16	10.0	7300	550	4000	375	375	1370	27.0	TT
14.00-24	24	10.0	9500	850	5150	575	375	1370	27.0	TT
14.00-24	28	10.0	10000	925	5600	650	375	1370	27.0	TT
14.00-25	28	10.00/1.5	10000	925	5600	650	375	1370	27.0	TT
14.00-25	36	10.00/1.5	11050	1100	5500	850	375	1370	27.0	TT



## EM01(E-3)

OTR Tire

1. Deep tread pattern ensure tyre life.
2. Wider tread blocks enhance traction performance.
3. Special compound design ,low heat-generation,excellent wear and tear resistance.
4. Available for large rigid dump trucks.

NEW

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
14.00-24	24	10.0	9500	850	5150	575	375	1370	34.0	TT
14.00-24	28	10.0	10000	925	5600	650	375	1370	34.0	TT
14.00-25	28	10.00/1.5	10000	925	5600	650	375	1370	33.0	TT



## LL26/E-3

OTR Tire

1. Available for large self-dumping trucks.
2. Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
18.00-25	32	13.00/2.5	15000	750	8750	575	500	1615	30.0	TT/TL
18.00-25	40	13.00/2.5	17000	950	9750	700	500	1615	30.0	TT/TL



## LL56(E-3)

OTR Tire

1. Available for large self-dumping trucks.
2. Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
18.00-25	32	13.00/2.5	15000	750	8750	575	500	1615	30.0	TT
18.00-25	36	13.00/2.5	16000	850	9250	625	500	1615	30.0	TT



## LL90(E-4)

OTR Tire

1. Available for large self-dumping trucks.
2. Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
18.00-33	32	13.00	17500	750	10000	575	500	1875	50.0	TL
18.00-33	36	13.00	18500	850	10600	625	500	1875	50.0	TL
18.00-33	40	13.00	19500	950	11200	700	500	1875	50.0	TL



## E-4

OTR Tire

- 1.Available for large self-dumping trucks.
- 2.Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
21.00-33	32	15.00/3.0	--	--	10300	500	570	1940	42.0	TL
21.00-33	42	15.00/3.0	--	--	12400	690	570	1940	42.0	TL



NEW

## EM02(E-4)

OTR Tire

- 1.Available for large self-dumping trucks.
- 2.Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
21.00-35	40	15.00/3.0	24300	825	14000	625	570	2050	60.0	TL
24.00-35	42	17.00/3.5	29000	750	16500	550	655	2175	60.0	TL



## E-4

OTR Tire

- 1.Available for large self-dumping trucks.
- 2.Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
21.00-35	32	15.00/3.0	21200	650	12150	500	570	2050	42.0	TL
21.00-35	36	15.00/3.0	23000	750	12850	550	570	2050	42.0	TL
21.00-35	40	15.00/3.0	24300	825	14000	625	570	2050	42.0	TL



## LL25(E-3)

OTR Tire

- 1.Available for large rigid dump trucks.
- 2.Wear resistance, good grip and self-cleaning performance.

Size	Ply Rating	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
16.00-25	28	11.25/2.0	11500	750	6700	575	430	1495	28.5	TT/TL
16.00-25	32	11.25/2.0	12500	875	7300	650	430	1495	28.5	TT/TL
16.00-25	36	11.25/2.0	13600	975	7750	725	430	1495	28.5	TT

# Underground Work



## LSM401(L-4S)

OTR Tire

- 1.Available for loaders operating under seriously tough service conditions in tunnels.
- 2.Excellent wear and cut resistance.
- 3.Flat and smooth tread improves the puncture resistance to stone.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Max Speed (km/h)	Type
10.00-20	14	--	--	7.5	3260	670	278	1073	35	10	TT
10.00-20	16	--	--	7.5	3535	770	278	1073	35	10	TT



## LSM401(L-4S+)

OTR Tire

- 1.Available for loaders operating under seriously tough service conditions in tunnels.
- 2.Excellent wear and cut resistance.
- 3.Flat and smooth tread improves the puncture resistance to stone.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Max Speed (km/h)	Type
10.00-20	14	--	--	7.5	3260	670	278	1073	45	10	TT
10.00-20	16	--	--	7.5	3535	770	278	1073	45	10	TT



## LSM402

OTR Tire

- 1.Special tread compound design,High wear resistance performance.
- 2.Wide tread arc and deep pattern design,Increase tyre life.
- 3.Sole sidewall protection design,Enhance puncture resistance performance.
- 4.Novel appearance.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Max Speed (km/h)	Type
9.00-20	14	--	--	7.0	4375	725	255	1015	35	10	TT
9.00-20	16	--	--	7.0	4750	825	255	1015	35	10	TT
10.00-20	16	--	--	7.5	3535	770	278	1073	45	10	TT
12.00-24	16	--	--	8.5	6150	675	315	1275	55	10	TT
12.00-24	18	--	--	8.5	6500	750	315	1275	55	10	TT
12.00-24	20	--	--	8.5	6900	825	315	1275	55	10	TT
12.00-24	24	--	--	8.5	7500	975	315	1275	55	10	TT
14.00-24	28	--	--	10.0	10000	925	375	1420	65	10	TT
17.5-25	20	--	--	14.00/1.5	8250	575	445	1400	65	10	TT/TL
17.5-25	24	--	--	14.00/1.5	9250	700	445	1400	65	10	TT/TL
17.5-25	32	--	--	14.00/1.5	11700	830	445	1400	65	10	TT/TL
18.00-25	32	--	--	13.00/2.5	15000	750	500	1675	85	10	TL
18.00-25	40	--	--	13.00/2.5	17000	950	500	1675	85	10	TL



# Loader



## LL25(E-3/L-3)

OTR Tire

- 1.Available for loaders and dozers.
- 2.Wear and puncture resistance.
- 3.Wide application.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
15.5-25	12	--	--	12.00/1.3	5600	400	3250	250	395	1275	25.0	TL
17.5-25	12	--	--	14.00/15	6150	350	3650	225	445	1350	25.5	TT/TL
17.5-25	16	--	--	14.00/15	7300	475	4250	300	445	1350	25.5	TT/TL
20.5-25	16	--	--	17.00/2.0	8250	350	5450	275	520	1490	28.5	TT/TL
20.5-25	20	--	--	17.00/2.0	9500	450	6000	325	520	1490	28.5	TT/TL
23.5-25	16	--	--	19.50/2.5	9500	300	6150	225	595	1615	31.5	TT/TL
23.5-25	18	--	--	19.50/2.5	10050	350	6700	275	595	1615	31.5	TT
23.5-25	20	--	--	19.50/2.5	10900	375	7300	300	595	1615	31.5	TT/TL
23.5-25	24	--	--	19.50/2.5	12500	475	8000	350	595	1615	31.5	TT/TL
26.5-25	20	--	--	22.00/3.0	13200	350	8250	250	675	1750	35.0	TT
26.5-25	24	--	--	22.00/3.0	14000	400	9250	300	675	1750	35.0	TL
26.5-25	28	--	--	22.00/3.0	15500	475	10000	350	675	1750	35.0	TT/TL
29.5-25	28	--	--	25.00/3.5	17500	425	11500	325	750	1875	40.0	TL



## LL136(E-3/L-3)

OTR Tire

- 1.Specialized pattern for sand and other soft surfaces.
- 2.High side-skid resistance and traction.
- 3.Excellent in self-cleaning,handling stability and driving comfot.
- 4.Larger contact area offers even wear and long life.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
23.5-25	16	--	--	19.50/2.5	9500	300	6150	225	595	1615	31.5	TT



## E-3/L-3

OTR Tyre

- 1.Suitable for heavy loaders used on bad road condition of mine,stone pit and tunnel,etc.
- 2.Good impale and wear resistance.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
29.5-29	28	--	--	25.00/3.5	19000	425	12150	325	750	1975	40.0	TL



## LL55(E-3)

OTR Tire

- 1.Available for loaders and dozers.
- 2.Wear and puncture resistance.
- 3.Wide application.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
16/70-20	10	--	--	13	4200	325	2400	250	410	1075	20.0	TT
16/70-20	14	--	--	13	5150	450	5150	450	410	1075	20.0	TT



## L301(E-3+)

OTR Tire

- 1.Deepen the pattern design, increase the service life of the tir.
- 2.Large tread pattern block design, uniform tread wear.
- 3.Special mine formula, anti cutting, anti tearing, super abrasion resistance.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
17.5-25	12	--	--	14.00/15	6150	350	3650	225	445	1350	36	TT
23.5-25	16	--	--	19.50/2.5	9500	300	6150	225	595	1615	45	TT

# Port



## LP401(IND-4)

Port Tire

- 1.Extra deep tread pattern ensure tyre life.
- 2.Wider tread blocks enhance traction performance.
- 3.Special compound design for ports,low heat-generation,excellent wear and tear resistance.

Size	Ply Rating	Rim	5km/h		10km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
14.00-24	28	10.0	14500	1000	13500	1000	375	1420	53.0	TT
16.00-25	36	11.25/2.0	19700	1000	18400	1000	430	1550	67.0	TL
18.00-25	40	13.00/2.5	24600	1000	22900	1000	500	1675	72.0	TL



## LP402(IND-3)

Port Tire

- 1.Extra deep tread pattern ensure tyre life.
- 2.Wider tread blocks enhance traction performance.
- 3.Special compound design for ports,low heat-generation,excellent wear and tear resistance.

Size	Ply Rating	Rim	5km/h		10km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
			Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
21.00-25	40	15.00/3.0	29310	1000	27290	1000	570	1750	44.0	TL

# Graders



## G-2

OTR Tire

- 1.Good steer and traction.
- 2.Off-road pattern has self-cleaning performance and comfort.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		40km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	TT/TL
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
13.00-24	12	--	--	8.00TG	5600	450	2725	300	335	1280	24.0	TL
13.00-24	18	--	--	8.00TG	6700	675	3500	450	335	1280	24.0	TL
14.00-24	12	--	--	8.00TG	6300	425	3075	275	360	1350	24.0	TT/TL
14.00-24	16	--	--	8.00TG	7300	550	3650	350	360	1350	24.0	TT/TL



## LG201(G-2)

OTR Tire

- 1.Good steer and traction.
- 2.Off-road pattern has self-cleaning performance and comfort.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		40km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	TT/TL
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
16.00-24	12	--	--	11.25/2.5	7100	325	3650	225	430	1490	28.5	TT
16.00-24	16	--	--	11.25/2.5	8250	425	4500	250	430	1490	28.5	TT
16.00-24	20	--	--	11.25/2.5	9250	525	5450	420	430	1490	28.5	TT



## E2/L2

OTR Tire

1. Good steer and traction.
2. Off-road pattern has self-cleaning performance and comfort.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	TT/TL
					Max.Load (kg)	Inflated Pressure (kPa)	Max.Load (kg)	Inflated Pressure (kPa)				
15.5-25	12	--	--	12.00/1.3	5600	400	3250	250	395	1275	24.0	TL
17.5-25	12	--	--	14.00/1.5	6150	350	3650	225	445	1350	25.5	TT/TL
17.5-25	16	--	--	14.00/1.5	7300	475	4250	300	445	1350	25.5	TT/TL
20.5-25	16	--	--	17.00/2.0	8250	350	5450	275	520	1490	28.5	TT/TL
20.5-25	20	--	--	17.00/2.0	9500	450	6000	325	520	1490	28.5	TT/TL
23.5-25	16	--	--	19.50/2.5	9500	300	6150	225	595	1615	31.5	TT/TL
23.5-25	20	--	--	19.50/2.5	10900	375	7300	300	595	1615	31.5	TT/TL
23.5-25	24	--	--	19.50/2.5	12500	475	8000	350	595	1615	31.5	TT



## LL66A

OTR Tire

1. Available for loaders operating under seriously tough service conditions in tunnels.
2. Excellent wear and cut resistance.
3. Flat and smooth tread improves the puncture resistance to stone.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	TT/TL
					Max.Load (kg)	Inflated Pressure (kPa)				
7.50-16	14	--	--	6.00G	2390	700	215	810	--	TT
12.00-24	16	--	--	8.5	6150	675	315	1245	--	TT
12.00-24	18	--	--	8.5	6500	750	315	1245	--	TT
12.00-24	20	--	--	8.5	6900	825	315	1245	--	TT

# Compactions



## LC101

OTR Tire

1. Available for loaders operating under seriously tough service conditions in tunnels.
2. Excellent wear and cut resistance.
3. Flat and smooth tread improves the puncture resistance to stone.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	TT/TL
					Max.Load (kg)	Inflated Pressure (kPa)				
13/80-20	16	--	--	9.0	5430	800	325	1045	--	TT



## LL66B

OTR Tire

1. Available for loaders operating under seriously tough service conditions in tunnels.
2. Excellent wear and cut resistance.
3. Flat and smooth tread improves the puncture resistance to stone.

Size	Ply Rating	Load Index	Speed Symbols	Rim	10km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	TT/TL
					Max.Load (kg)	Inflated Pressure (kPa)				
9.00-20	14	--	--	7.0	4375	725	255	1015	--	TT

# Forestry



## LL711

### Logging Tire

- 1.Available for logging transport of short haul.
- 2.Good running stability and powerful grip.
- 3.Powerful resistance to wear,cut and attack.
- 4.Good traction.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)
12.00-24	20	--	--	8.5	4495	750	315	1275	36.0



## LML401

### Logging Tire

- 1.Available for logging transport of short haul.
- 2.Good running stability and powerful grip.
- 3.Powerful resistance to wear,cut and attack.
- 4.Good traction.

Size	Ply Rating	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)
11.00-20	16	--	--	8.0	3350	810	293	1131	32.0
11.00-20	18	--	--	8	3650	910	293	1131	32.0

# Sand



## LD701

- 1.Available for gravel road.
- 2.Good delivery performance.
- 3.Low rolling resistance and good heat dissipation.
- 4.Lateral grip.

Size	Ply Rating	Load Index	Speed Symbols	Rim	50km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
					Max.Load (kg)	Inflated Pressure (kPa)				
18-20	14	--	--	14.00T	4625	360	455	1090	16	TT/TL
20-20	16	--	--	14.00T	6000	360	505	1180	17	TL
22-20	14	--	--	17.0	4125	280	555	1075	18	TL



## LL200

- 1.Available for gravel road.
- 2.Good delivery performance.
- 3.Low rolling resistance and good heat dissipation.
- 4.Lateral grip.

Size	Ply Rating	Load Index	Speed Symbols	Rim	65km/h		Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
					Max.Load (kg)	Inflated Pressure (kPa)				
9.00-15	8	--	--	5.50F	945	245	235	840	8.0	TT
9.00-16	8	--	--	6.50H	985	245	245	890	8.0	TT
14.00-20	20	--	--	10.00W	2635	345	375	1220	8.5	TT