



GL699

High Handling Performance,Wet Excellent Resistance

- 1.Mobile single rotation pattern provides enduring, stable and comfortable driving.
- 2.The speed per hpur is above 240km/h.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
195/50R15	82	V	6J	475	250	577	201	8.0



INF-201

Single Direction, High Handling Performance

- 1.Direction tread pattern design reduce the rolling resistance and improve the High handling performance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
255/60R15	102	H	7 1/2J	850	250	687	260	8.7
255/65R16	109	H	7 1/2J	1030	250	738	260	8.7
275/60R15	107	H	8J	975	250	711	279	8.7
275/60R16	109	H	8J	1030	250	736	279	8.7
295/50R15	108	S	9 1/2J	1000	250	677	309	8.7
295/50R16	109	S	9 1/2J	1030	250	702	309	8.7



LMB3

All Terrain And High Mileage Performance

- 1.The tire is suitable for all terrain.
- 2.High mileage with wear resistance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
215/75R15	100	S	6J	800	250	703	216	9.5
P235/75R15	105	S	6 1/2J	925	250	733	235	10.0



INF-200

High Handing And Wet Grip Performance

- 1.The designed pattern blocks ensure the driving power on various road surfaces.
- 2.The grooves of big angles increase the three-dimensional appeal and guarantee drainage.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
					kg	kPa	mm	mm	mm
205/70R15	/	96	H	6J	710	250	669	209	10.2
215/65R16	/	98	H	6 1/2J	750	250	686	221	10.2
215/70R16	/	100	T	6 1/2J	800	250	708	221	10.2
235/65R17 XL	/	108	H/V	7J	1000	290	738	240	10.2
235/70R16	/	106	H/T	7J	950	250	736	240	10.2
245/65R17	/	107	H	7J	975	250	750	248	10.7
245/70R16	/	107	H	7J	975	250	750	248	10.2
265/70R15	/	112	H	8J	1120	250	753	272	10.2
265/70R16	/	112	H	8J	1120	250	778	272	10.2
275/55R17	/	109	V	8 1/2J	1030	250	734	284	10.2
275/70R16	/	114	H	8J	1180	250	792	279	10.2



INF-05

High Handling Performance

- 1.Wider ground area and larger pattern sea/land ratio, to ensure that the tire still has excellent grip and handling performance on wet road.
- 2.Continuous shoulder pattern block with special sidewall design,ensure that the tire still have a good performance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
205/40R17 XL	84	W	7 1/2J	500	290	596	212	7.8
205/45R16 XL	87	W	7J	545	290	590	206	7.8
205/45R17	84	W	7J	500	250	616	206	7.8
205/50R16 XL	91	W	6 1/2J	615	290	612	214	7.8
205/50R17 XL	93	W	6 1/2J	650	290	638	214	7.8
205/55R16 XL	94	W	6 1/2J	670	290	632	214	7.8
215/40R16 XL	86	W	7 1/2J	530	290	578	218	7.8
215/40R17 XL	87	W	7 1/2J	545	290	604	218	7.8
215/45R17 XL	91	W	7J	615	290	626	213	7.8
215/50R17	91	W	7J	615	250	648	226	7.8
215/55R16 XL	97	W	7J	730	290	642	226	7.8
225/40R18 XL	92	W	8J	630	290	637	230	7.8
225/45R16	89	W	7 1/2J	580	250	608	225	7.8
225/45R17 XL	94	W	7 1/2J	670	290	634	225	7.8
225/50R16 XL	96	W	7J	710	290	632	233	7.8
225/55R16	95	V	7J	690	250	654	233	7.8
225/55R16 XL	99	W	7J	775	290	654	233	7.8
235/40R17	90	W	8 1/2J	600	250	620	241	7.8
235/40R18 XL	95	W	8 1/2J	690	290	645	241	7.8
235/45R17 XL	97	W	8J	730	290	644	236	7.8
235/60R16	100	W	7J	800	250	688	240	7.8
245/40R17	91	W	8 1/2J	615	250	628	248	7.8
245/45R18 XL	100	W	8J	800	250	677	243	7.8





ENVIRO

High Handling Performance

- 1.Handling:super wide contact area and lower void volume provide excellent grip and handling performance on snow;A solid center rib enhances ascendant handling stability.
- 2.Grip:Design of irregular pattern and small grooves and transverse grooves near center reduces hydroplaning effectively and improve grip performance of tyre.
- 3.Wet grip: Four circumferential grooves can drain water effectively even on seeper road which makes driving safe.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
205/80R16 XL	104	T	5 1/2J	900	280	734	203	8.5
215/60R17	96	H	6 1/2J	710	250	690	221	8.5
215/65R16	98	H	6 1/2J	750	250	686	221	8.5
225/60R17 XL	103	V	6 1/2J	875	290	702	228	8.2
225/65R17	102	H	6 1/2J	850	250	724	228	8.5
235/50R18	97	V	7 1/2J	730	250	693	245	8.2
235/55R17	99	H	7 1/2J	775	250	690	245	8.2
235/55R17 XL	103	V	7 1/2J	875	290	690	245	8.2
235/55R18 XL	104	V	7 1/2J	900	290	715	245	8.5
235/60R16	100	H	7J	800	250	688	240	8.5
235/60R18 XL	107	V	7J	975	290	739	240	8.5
235/65R17 XL	108	V	7J	1000	290	738	240	8.5
245/45R20 XL	103	W	8J	875	290	728	243	8.2
255/50R19 XL	107	Y	8J	975	290	739	265	8.2
255/50R19XL	107	W	8J	975	290	739	265	8.2
255/55R18 XL	109	Y	8J	1030	290	737	265	8.2
255/55R18 XL	109	W	8J	1030	290	737	265	8.2
265/65R17	112	H	8J	1120	250	776	272	8.5
275/40R20 XL	106	Y	9 1/2J	950	290	728	278	8.2
275/45R20 XL	110	W	9J	1060	290	756	273	8.2



ECOTREK

Suitable For Urban Highway

High Handling,Low Noise Performance

- 1.Viable pattern pitches reduce noise and provides a quiet and comfort ride.
- 2.Four wide grooves improve water evacuation and effectively reduce aquaplaning.
- 3.The center pattern rib ensures a superior lateral handling; the sipes on the rib provide comfort ride.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
205/70R15	96	H	6J	710	250	669	209	8.2
205/80R16 XL	104	T	5 1/2J	900	280	734	203	8.2
215/70R16	100	H	6 1/2J	800	250	708	221	8.2
225/70R16	103	H	6 1/2J	875	250	722	228	8.2
235/70R16	106	H	7J	950	250	736	240	8.2
235/75R15	105	H	6 1/2J	925	250	733	235	8.2
245/70R16 XL	111	H	7J	1090	290	750	248	8.2





ECOGRIP

All-weather Abrasion Resistance Tires, Wet Excellent Resistance

- 1.Tire shoulder and tire crown pattern with double set of defection from the combination of decorative pattern design to reduce the noise at the same time, improve the tire abrasion performance.
- 2.Central tire crown and tire shoulder to strengthen, enhance the whole tire crown stiffness, beneficial to the improvement of the tire to stability and abrasion.
- 3.No specifications block design of old decorative pattern, trench wall Angle is diversiform, can effectively eliminate pattern groove with dirt and gravel, improve through sex.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
					kg	kPa	mm	mm	mm
225/65R17	/	102	T	6 1/2J	850	250	724	228	9.2
225/70R16	/	103	T	6 1/2J	875	250	722	228	9.2
225/75R16	/	104	Q	6 1/2J	900	250	744	223	9.2
235/60R16	/	100	T	7J	800	250	688	240	9.2
235/75R15 XL	/	109	T	6 1/2J	1030	290	733	235	9.2
245/70R17	/	110	Q	7J	1060	250	776	248	11.0
265/75R16	/	116	T	7 1/2J	1250	250	804	267	11.0
31X10.5R15LT	6	109	R	8 1/2J	1030	350	775	268	12.7
31X10.5R15LT	6	109	Q	8 1/2J	1030	350	775	268	12.7
LT215/75R15	6	100/97	R	6J	D730 S800	350	703	216	12.7
LT235/75R15	6	104/101	R	6 1/2J	D825 S900	350	733	235	12.7
LT235/85R16	10	120/116	R	6 1/2J	D1250 S1400	550	806	235	12.7
LT235/85R16	10	120/116	Q	6 1/2J	D1250 S1400	550	806	235	12.7
LT245/75R16	10	120/116	Q	7J	D1250 S1400	550	774	248	12.7
LT265/70R17	10	121/118	R	8J	D1320 S1450	550	804	272	12.7
LT265/70R17	10	121/118	Q	8J	D1320 S1450	550	804	272	12.7
LT265/75R16	10	123/120	R	7 1/2J	D1400 S1550	550	804	267	12.7
LT265/75R16	10	123/120	Q	7 1/2J	D1400 S1550	550	804	267	12.7
LT275/65R18	10	123/120	Q	8J	D1400 S1550	550	815	279	12.7
LT285/70R17	8	121/118	Q	8 1/2J	D1320 S1450	450	832	292	12.7
LT285/75R16	10	126/123	Q	8J	D1550 S1700	550	834	286	12.7
LT315/75R16	8	121/118	Q	8 1/2J	D1320 S1450	350	878	313	12.7

Light Truck Tire





ECOVANTAGE

High Wear Performance

- 1.The ECOVANTAGE for light fleets is suitable for use on vans and similar vehicles.
- 2.Its driving properties are excellent even at high speeds and with heavy loads.
- 3.High-performance friction type for all of the market especially for Central European.
- 4.Pronounced grooves in the central region—Good drainage—Resistance to.
- 5.hydroplaning.
- 6.Huge block enhances the should stiffnessand resistance to irregular wear.
- 7.New compound, to meet tread wear and wet performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
					kg	kPa	mm	mm	mm
175/65R14C	6	90/88	T	5J	D560 S600	375	584	177	7.8
185/75R16C	8	104/102	R	5J	D850 S900	475	684	184	9.2
185/85R16LT	8	105/103	Q	5J	D875 S925	450	720	186	9.2
195/65R16C	8	104/102	T	6J	D850 S900	475	660	201	9.0
195/70R14C	8	101/99	T	6J	D775 S825	475	630	201	9.2
195/70R15C	8	104/102	R	6J	D850 S900	450	655	201	9.7
195/75R16C	8	107/105	R	5 1/2J	D925 S975	475	698	196	9.7
205/65R16C	8	107/105	T	6J	D925 S975	475	672	209	9.2
215/60R16C	6	103/101	T	6 1/2J	D825 S875	375	664	221	9.2
215/65R16C	8	109/107	T	6 1/2J	D975 S1030	475	686	221	9.2
215/75R16C	10	116/114	R	6J	D1180 S1250	525	728	216	9.2
225/65R16C	8	112/110	R	6 1/2J	D1060 S1120	475	698	228	9.2
225/70R15C	8	112/110	R	6 1/2J	D1060 S1120	450	697	228	9.7
225/70R15C	8	112/110	S	6 1/2J	D1060 S1120	450	697	228	9.7
235/65R16C	8	115/113	R	7J	D1150 S1215	475	712	240	9.2



INF-66

High Cornering And Abrasion Performance

- 1.The design of tread pattern with three wide and deep groove can improve the drainage ability and the stability under transport condition, beyond that, it has lower noise and good abrasion performance.
- 2.The soft sidewall can realize a perfect combination between safety and comfort.
- 3.The strong tire shoulder can provide excellent cornering performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
					kg	kPa	mm	mm	mm
5.00R12LT	8	83/81	N	3.50B	D462 S487	450	571	135	8.0



INF-100

Excellent Traction And Handling Performance

- 1.Streamlined transverse pattern provides excellent traction and handling performance.
- 2.Long life.
- 3.Excellent endurance performance suits long haul and all terrain.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
165/70R14C	89/87	R	5J	D545 S580	375	588	170	8.5
175/75R16C	101/99	R	5J	D775 S825	475	668	177	8.5
185/75R16C	104/102	R	5J	D850 S900	475	684	184	8.5
185R14C	102/100	N	5 1/2J	D800 S850	450	650	188	8.5
195/65R16C	104/102	R	6J	D850 S900	475	660	201	8.5
195/70R15C	104/102	R	6J	D850 S900	450	655	201	9.5
195/75R16C	107/105	R	5 1/2J	D925 S975	475	698	196	8.5
205/65R16C	107/105	R	6J	D925 S975	475	672	209	9.5
205/75R16C	110/108	R	5 1/2J	D1000 S1060	475	714	203	9.5
215/65R16C	109/107	R	6 1/2J	D975 S1030	475	686	221	9.5
215/75R16C	113/111	R	6J	D1090 S1150	475	728	216	9.5
225/65R16C	112/110	R	6 1/2J	D1060 S1120	475	698	228	9.5
225/70R15C	112/110	R	6 1/2J	D1060 S1120	475	697	228	9.5
225/75R16C	121/120	R	6J	D1400 S1450	575	744	223	9.5
235/65R16C	115/113	R	7J	D1150 S1215	475	712	240	9.5



INF-CR034

High Cornering And Abrasion Performance

- 1.The strong tire shoulder can provide excellent cornering performance.
- 2.The soft sidewall can realize a perfect combination between safety and comfort.
- 3.The deeper pattern groove can improve the excellent abrasion ability.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
					kg	kPa	mm	mm	mm
7.50R16	14	122/118	Q	6.00G	D1320 S1500	770	805	215	11.0



LMB3

All Terrain And High Mileage Performance

- 1.The tire is suitable for all terrain.
- 2.High mileage with wear resistance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
195/70R15C(WHITE)	104/102	R	6J	D850 S900	450	655	201	9.5
195/70R15C	104/102	R	6J	D850 S900	450	655	201	9.5



LMC5

Good Drainage And Handling Stability Performance

- 1.Good handling stability.
- 2.Excellent traction and lateral skid prevention.
- 3.Good drainage with open designed pattern.
- 4.Suitable for all terrain especially for crossing country.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
185R14C	102/100	N/Q/R	5 1/2J	D800 S850	450	650	188	10.5
195R14C	106/104	P	5 1/2J	D900 S950	450	666	198	10.5



RADIAL616

Excellent Traction And Handling Performance

- 1.High mileage and wear resistance.
- 2.Good handling in high speed.
- 3.Excellent traction while running on snow and ice.
- 4.High performance tire with crosscountry pattern suit to all terrain.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
30×9.50R15LT	104	Q	7 1/2J	900	350	750	240	11.5
31×10.50R15LT	109	Q	8 1/2J	1030	350	775	268	11.5



INF-200

High Handing And Wet Grip Performance

- 1.The designed pattern blocks ensure the driving power on various road surfaces.
- 2.The grooves of big angles increase the three-dimensional appeal and guarantee drainage.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
					kg	kPa	mm	mm	mm
195R15C	8	106/104	Q	5 1/2J	D900 S950	450	693	196	9.2
LT225/75R16	10	115/112	Q	6J	D1120 S1215	550	744	223	10.8
LT235/85R16	10	120/116	Q	6 1/2J	D1250 S1400	550	806	235	10.8
LT245/75R16	6	108/104	Q	7J	D900 S1000	350	774	248	10.8



LMC8

High Cornering And Abrasion Performance

- 1.The super physical design, shockproof and wear resistance.
- 2.Good turning and road-surface controlling ability.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
195R14C(WHITE)	106/104	P	5 1/2J	D900 S950	450	666	198	9.5
195R14C	106/104	P	5 1/2J	D900 S950	450	666	198	9.5
205R14C	109/107	R	6J	D975 S1030	450	686	208	9.5
205R15C	110/108	R	6J	D1000 S1060	450	710	208	9.5

Winter Tire



ECOSNOW

High Snow Handling Performance

- 1.Decorative pattern design help stabilize the straight direction type to drive performance and handling on the surface of the snow.
- 2.Winding and transverse groove design to improve handling in the snow.
- 3.Serrated steel design shortened braking distance in the snow and ice, improve the brake and surface performance on the ice.
- 4.The steel in the shoulder increased hardness block, on the ice to handling and steering performance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
175/65R14	82	T	5J	475	250	584	177	9.7
175/70R13	82	T	5J	475	250	576	177	9.7
185/60R15 XL	88	T	5 1/2J	560	290	603	189	9.7
185/65R14	86	T	5 1/2J	530	250	596	189	9.7
185/65R15	88	T	5 1/2J	560	250	621	189	9.7
185/70R14	88	T	5 1/2J	560	250	616	189	9.7
205/55R16 XL	94	T	6 1/2J	670	290	632	214	9.7
205/60R16 XL	96	T	6J	710	290	652	209	9.7
205/65R15	94	T	6J	670	250	647	209	9.7
215/55R16 XL	97	T	7J	730	290	642	226	9.7
215/65R16 XL	102	T	6 1/2J	850	290	686	221	9.7



ECOSNOW SUV

High Snow Handling Performance

- 1.Decorative pattern design help stabilize the straight direction type to drive performance and handling on the surface of the snow.
- 2.Winding and transverse groove design to improve handling in the snow.
- 3.Serrated steel design shortened braking distance in the snow and ice, improve the brake and surface performance on the ice.
- 4.The steel in the shoulder increased hardness block, on the ice to handling and steering performance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
205/70R15	96	T	6J	710	250	669	209	9.7
215/70R16	100	T	6 1/2J	800	250	708	221	9.7
225/70R16	103	T	6 1/2J	875	250	722	228	9.7
225/75R16	104	T	6J	900	250	744	223	9.7
235/65R17 XL	108	T	7J	1000	290	738	240	9.7
235/75R15 XL	109	T	6 1/2J	1030	290	733	235	9.7
245/70R16	107	T	7J	975	250	750	248	9.7
255/55R18 XL	109	T	8J	1030	290	737	265	9.7
265/70R16	112	T	8J	1120	250	778	272	9.7



ECOZEN

The Tire Is Suitable For Snow, Which Has Excellent Handing And Holding Performance

- 1.Wider ground area and larger pattern sea/land ratio, to ensure that the tire still has excellent grip and handling performance on wet road.
- 2.The rationalization of the groove depth design can let snow out well.
- 3.Special tread compound desin can supply much better grip to prmote tire safe and handling performance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
155/65R14	75	T	4 1/2J	387	250	558	157	8.2
165/65R14	79	T	5J	437	250	570	170	8.2
175/65R15	84	T	5J	500	250	609	177	8.2
185/55R15 XL	86	H	6J	530	290	585	194	8.5
185/60R15 XL	88	H	5 1/2J	560	290	603	189	8.5
195/55R16 XL	91	H	6J	615	290	620	201	8.5
195/65R15 XL	95	T	6J	690	290	635	201	8.5
205/50R17 XL	93	V	6 1/2J	650	290	638	214	8.5
205/55R16 XL	94	H	6 1/2J	670	290	632	214	8.5
215/50R17 XL	95	V	7J	690	290	648	226	8.5
215/55R16 XL	97	H	7J	730	290	642	226	8.5
215/65R16	98	H	6 1/2J	750	250	686	221	8.5
225/40R18 XL	92	V	8J	630	290	637	230	8.8
225/50R17 XL	98	V	7J	750	290	658	233	8.8
225/55R16 XL	99	H	7J	775	290	654	233	8.8
225/55R17 XL	101	V	7J	825	290	680	233	8.8
245/45R18 XL	100	V	8J	800	290	677	243	8.8



INF-049

The Tire Is Suitable For Snow, Which Has Excellent Handing And Holding Performance

- 1.Special sipe design and stiffness of effectively proportionated pattern blocks guarantee outstanding cornering and handling performance.
- 2.Special tread compound desin can supply much better grip to prmote tire safe and handling performance.

Size	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
				kg	kPa	mm	mm	mm
155/70R13	75	T	4.50B	387	250	548	157	8.4
155/80R13	79	T	4.50B	437	240	578	157	8.4
165/70R13	79	T	5.00B	437	250	562	170	8.5
165/70R14	81	T	5J	462	250	288	170	8.4
175/65R14	82	T	5J	475	250	584	177	8.4
175/70R13	82	T	5.00B	475	250	576	177	8.4
175/70R14	84	T	5J	500	250	602	177	8.4
185/60R14	82	T	5 1/2J	475	250	578	189	8.4
185/65R14	86	T	5 1/2J	530	250	596	189	8.4
185/65R15	88	T	5 1/2J	560	250	621	189	8.4
195/50R15	82	H	6J	475	250	577	201	8.7
195/55R15	85	H	6J	515	250	595	201	8.4
195/60R14	86	H	6J	530	250	590	201	8.7
195/60R15	88	H	6J	560	250	615	201	8.7
195/60R15	88	T	6J	560	250	615	201	8.7
195/65R15	91	H	6J	615	250	635	201	8.7
195/65R15	91	T	6J	615	250	635	201	8.7
205/55R16	91	H	6 1/2J	615	250	632	214	8.7
205/60R16	92	H	6J	630	250	652	209	8.7
205/65R15	94	H	6J	670	250	647	209	8.7
215/55R16	93	H	7J	650	250	642	226	8.7
215/55R17	98	H	7J	750	250	668	226	8.7
215/60R16 XL	99	H	6 1/2J	775	290	664	221	8.7
215/65R16	98	T	6 1/2J	750	250	686	221	8.7
215/70R15	98	S	6 1/2J	750	250	683	221	8.7
225/45R17 XL	94	W	7 1/2J	670	290	634	225	9
225/50R17	94	H	7J	670	250	658	233	8.7
225/60R16 XL	102	V	6 1/2J	850	290	676	228	8.7
225/60R17	99	H	6 1/2J	775	250	702	228	8.7
225/65R17	102	T	6 1/2J	850	250	724	228	9.7
235/70R16 XL	109	T	7J	1030	290	736	240	10.2
265/70R17	115	H	8J	1215	250	804	272	10.2



INF-059

High Snow And Handling Performance

- 1.Wide footprint area and larger pattern sea/land ratio, to ensure that the tire still has excellent grip and handling performanceon wet pavement snow.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Standard Load	Inflated Pressure	Overall Diameter	Overall Width	Tread Depth
					kg	kPa	mm	mm	mm
185R14C	8	102/100	Q	5 1/2J	D800 S850	450	650	188	9.7
195/70R15C	8	104/102	Q	6J	D850 S900	450	655	201	10.7
205/65R16C	8	107/105	R	6J	D925 S975	475	672	209	10.7
215/65R16C	8	109/107	R	6 1/2J	D975 S1030	475	686	221	11.2
225/70R15C	8	112/110	R	6 1/2J	D1060 S1120	450	697	228	11.2

