

SPECIALTY TIRE

Industrial
Tire



Industrial



LF401

Industrial Tire

- 1.Wear resistance compound,High wear resistance performance. Increase tyre life.
- 2.Deep pattern design and wide tread arc,Enhance self-cleaning performance.
- 3.Variational pattern design,Novel appearance.
- 4.New stamping design.

NEW

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
18X7-8NHS	16	--	--	4.33R	1695	1000	173	465	18.0	TT
5.00-8NHS	10	--	--	3.50D	1150	1000	137	470	15.0	TT
6.00-9NHS	10	--	--	4.00E	1505	860	160	540	15.0	TT
6.50-10NHS	10	--	--	5.00F	1655	790	175	590	16.0	TT
7.00-12NHS	12	--	--	5.00S	2375	860	190	676	21.0	TT
28X9-15NHS (8.15-15)	14	--	--	7.0	3050	970	220	710	18.0	TT
8.25-15NHS	14	--	--	6.5	3775	830	235	840	23.0	TT
250-15NHS	18	--	--	7.5	4110	1030	250	735	23.5	TT
300-15NHS	18	--	--	8.0	5530	830	300	840	23.5	TT
7.50-16NHS	12	--	--	6.00G	3195	790	215	805	22.0	TT
9.00-20NHS	16	--	--	7.0	5195	760	259	1018	25.0	TT



LL39

Industrial Tire

- 1.Good wear and crack resistance.
- 2.Lateral grip.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
18x7-8NHS	16	--	--	4.33R	1640	1000	173	465	16.0	TT
6.50-10NHS	10	--	--	5.00F	1655	790	175	590	15.0	TT
6.50-10NHS	14	--	--	5.00F	1975	1070	175	590	15.0	TT
7.00-15NHS	12	--	--	5.50S	2900	850	194	735	20.0	TT
28X9-15NHS 8.15-15NHS	12	--	--	7.0	3230	840	215	704	16.0	TT
28x9-15NHS	14	--	--	7.0	3050	970	220	710	13.0	TT



LL45

Industrial Tire

- 1.Good wear and side slip resistance.
- 2.Stable performance.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
5.00-8NHS	6	--	--	3.50D	850	600	137	470	12.0	TT
5.00-8NHS	10	--	--	3.50D	1150	1000	137	470	12.0	TT
6.00-9NHS	10	--	--	4.00E	1505	860	160	540	10.0	TT
6.50-10NHS	10	--	--	5.00F	1655	790	175	590	15.0	TT
7.00-9NHS	10	--	--	5.00S	1995	860	190	590	12.0	TT
7.00-12NHS	12	--	--	5.00S	2375	860	190	676	12.0	TT
7.50-15NHS	14	--	--	6.0	3375	925	215	780	18.0	TT
8.25-12NHS	12	--	--	6.5	3060	720	235	765	12.0	TT
8.25-15NHS	14	--	--	6.5	3775	830	235	840	15.0	TT
8.25-15NHS	18	--	--	6.5	4240	1000	235	840	15.0	TT
9.00-16NHS	14	--	--	6.50H	4495	760	255	890	16.0	TT



LL65

Industrial Tire

- 1.Wear and crack resistance.
- 2.Lateral grip.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
10.00-15NHS	14	--	--	7.5	2800	750	280	935	12.0	TT

Solid



LL102

Industrial Tire

- 1.Wear and crack resistance.
- 2.Low rolling resistance.
- 3.Good heat dissipation.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
10-16.5NHS	10	--	--	8.25	2135	520	264	773	13.0	TL
10-16.5NHS	12	--	--	8.25	2375	620	264	773	13.0	TL
12-16.5NHS	12	--	--	9.75	2865	550	307	831	13.0	TL



LL103

Industrial Tire

- 1.Wear and crack resistance.
- 2.Low rolling resistance.
- 3.Good heat dissipation.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
12-16.5LT	10	--	--	9.75	D1418 S1614	420	307	831	13.0	TL
12-16.5LT	12	--	--	9.75	D1650 S1850	520	307	831	13.0	TL



LL2

Industrial Tire

- 1.Good wear and crack resistance.
- 2.Lateral grip.

Size	Ply Rating	Load Index	Speed Symbols	Standard Rim	Max.Load (kg)	Inflated Pressure (kPa)	Section Width (mm)	Overall Diameter (mm)	Tread Depth (mm)	Type
9.00-16NHS	14	--	--	6.50H	4080	750	255	890	12.5	TT
9.00-16NHS	14	--	--	6.50H	2635	750	255	890	12.5	TT



LS601

Solid Tire for Fork Lifts

- 1.High traction.
- 2.Excellent stability.
- 3.Smooth running.
- 4.Wear&cut resistant tread compound.
- 5.Reinforced bead for secure mounting.
- 6.Three compound and nylon reinforced construction.

Size	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
					Balance Forklift				Other Industrial Vehicles		
					10km/h		16km/h		25km/h		10km/h
Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel						
5.00-8	3.00D	457	114	21	1255	965	1145	880	1060	815	960
18X7-8	4.33R	457	145	20	2430	1870	2215	1705	2060	1585	1870
6.00-9	4.00E	528	140	24	1975	1520	1805	1390	1675	1290	1520
6.50-10	5.00F	580	156	22	2715	2090	2485	1910	2310	1775	2090
7.00-12	5.00S	663	168	25	3105	2390	2835	2180	2635	2025	2095
28X9-15 (8.15-15)	7.0	706	215	27	4060	3125	3710	2855	3445	2650	3125
8.25-15	6.5	817	205	32	5085	3910	4640	3570	4310	3315	3910
7.00-15	5.5	759	204	30	3700	2845	3375	2595	3135	2410	2845



LS602

Solid Tire For Fork Lifts

- 1.Longitudinal pattern design,lightweight flexible,suitable for small vehicle.
- 2.Special tread compound formula,tire has good guidance ,high abrasion resistance and low rolling resistance and other properties.

Size	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
					Balance Forklift				Other Industrial Vehicles		
					10km/h		16km/h		25km/h		10km/h
Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel						
4.00-8	3.00D	412	116	5	1090	840	995	765	925	710	840
4.00-8	3.75A	412	116	5	1175	905	1080	830	1000	770	910



LS603

Solid Tire for Fork Lifts

- 1.High traction.
- 2.Excellent stability.
- 3.Smooth running.
- 4.Wear&cut resistant tread compound.
- 5.Reinforced bead for secure mounting.
- 6.Three compound and nylon reinforced construction.

Size	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
					Balance Forklift						Other Industrial Vehicles
					10km/h		16km/h		25km/h		10km/h
					Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	
16X6-8	4.33R	410	146	18	1545	1190	1410	1085	1305	1005	1185
23X9-10	6.50F	588	206	24	3730	2870	3405	2620	3160	2430	2865
250-15	7.0	713	226	25	5220	4015	4770	3670	4425	3405	4015
300-15	8.0	813	258	30	6895	5305	6300	4845	5850	4500	5310



LS605

Solid Tire for Fork Lifts

- 1.High traction.
- 2.Excellent stability.
- 3.Smooth running.
- 4.Wear&cut resistant tread compound.
- 5.Reinforced bead for secure mounting.
- 6.Three compound and nylon reinforced construction.

Size	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
					Balance Forklift						Other Industrial Vehicles
					10km/h		16km/h		25km/h		10km/h
					Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	
15x4½-8	3.00D	380	114	17	930	750	910	680	850	640	650
18x7-8	4.33R	456	162	25	2430	1870	2215	1705	2060	1585	1870
21x8-9	6.00E	535	202	30	2890	2225	2645	2035	2455	1890	2230
6.50-10	5.00F	597	178	30	2715	2090	2485	1910	2310	1775	2090
28X9-15 (8.15-15)	7.0	706	225	34	4060	3125	3710	2855	3445	2650	3125
8.25-15	6.5	847	236	38	5085	3910	4640	3570	4310	3315	3910



LS604

Solid Tire for Fork Lifts

- 1.High traction.
- 2.Excellent stability.
- 3.Smooth running.
- 4.Wear&cut resistant tread compound.
- 5.Reinforced bead for secure mounting.
- 6.Three compound and nylon reinforced construction.

Size	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
					Balance Forklift						Other Industrial Vehicles
					10km/h		16km/h		25km/h		10km/h
					Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	
200/50-10	6.50F	456	196	15	2910	2240	2665	2050	2470	1900	2240
23X10-12	8.00G	588	232	20	4450	3425	4060	3125	3770	2900	3420



LS605(RV)

Solid Tire for Fork Lifts

- 1.High traction.
- 2.Excellent stability.
- 3.The tire with damping hole, vehicle ride comfort is higher and can reduce the tire heat prolonging the service life of tires.
- 4.Wear&cut resistant tread compound.
- 5.Reinforced bead for secure mounting.
- 6.Three compound and nylon reinforced construction.

Size	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
					Balance Forklift						Other Industrial Vehicles
					10km/h		16km/h		25km/h		10km/h
					Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	
28X9-15 (8.15-15)	7.0	706	225	34	4060	3125	3710	2855	3445	2650	3125
8.25-15	6.5	847	236	38	5085	3910	4640	3570	4310	3315	3910



Non -marking solid tyres

Solid Tire for Fork Lifts

- 1.Chunk Resistant Non-Marking.
- 2.Excellent stability.
- 3.Smooth running.
- 4.Wear&cut resistant tread compound.
- 5.Reinforced bead for secure mounting.
- 6.Three compound and nylon reinforced construction.



Clip solid tyres

- 1.Low rolling resistance, traction is strong.
- 2.Excellent stability.
- 3.Abrasion resistant cutting performance.
- 4.Simple type bead design, safety light rim assembly.
- 5.Three compound and nylon reinforced construction.

Size	Pattern	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
						Balance Forklift						Other Industrial Vehicles
						10km/h		16km/h		25km/h		
						Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	
4.00-8	LS602	3.00D	412	116	5	1090	840	995	765	925	710	840
4.00-8	LS602	3.75A	412	116	5	1175	905	1080	830	1000	770	910
5.00-8	LS601	3.00D	457	114	21	1255	965	1145	880	1060	815	960
15x4½-8	LS605	3.00D	380	114	17	930	750	910	680	850	640	650
16X6-8	LS603	4.33R	410	146	18	1545	1190	1410	1085	1305	1005	1185
18X7-8	LS601	4.33R	457	145	20	2430	1870	2215	1705	2060	1585	1870
18x7-8	LS605	4.33R	457	162	25	2430	1870	2215	1705	2060	1585	1870
6.00-9	LS601	4.00E	528	140	24	1975	1520	1805	1390	1675	1290	1520
21x8-9	LS605	6.00E	535	202	30	2890	2225	2645	2035	2455	1890	2230
6.50-10	LS601	5.00F	580	156	22	2715	2090	2485	1910	2310	1775	2090
6.50-10	LS605	5.00F	597	178	30	2715	2090	2485	1910	2310	1775	2090
200/50-10	LS604	6.50F	456	196	15	2910	2240	2665	2050	2470	1900	2240
23X9-10	LS603	6.50F	588	206	24	3730	2870	3405	2620	3160	2430	2865
7.00-12	LS601	5.00S	663	168	25	3105	2390	2835	2180	2635	2025	2095
23X10-12	LS604	8.00G	588	232	20	4450	3425	4060	3125	3770	2900	3420
7.00-15	LS601	5.5	759	204	30	3700	2845	3375	2595	3135	2410	2845
28X9-15 (8.15-15)	LS601	7.0	706	215	27	4060	3125	3710	2855	3445	2650	3125
28X9-15 (8.15-15)	LS605	7.0	706	225	34	4060	3125	3710	2855	3445	2650	3125
8.25-15	LS601	6.5	817	205	32	5085	3910	4640	3570	4310	3315	3910
8.25-15	LS605	6.5	847	236	38	5085	3910	4640	3570	4310	3315	3910
250-15	LS603	7.0	713	226	25	5220	4015	4770	3670	4425	3405	4015
300-15	LS603	8.0	813	258	30	6895	5305	6300	4845	5850	4500	5310

Size	Pattern	Rim	Overall Diameter (mm)±3%	Section Width (mm)	Tread Depth (mm)	Max.Load (kg)						
						Balance Forklift						Other Industrial Vehicles
						10km/h		16km/h		25km/h		
						Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	Load Wheel	Steer Wheel	
15x4½-8	LS605	3.00D	380	114	17	930	750	910	680	850	640	650
5.00-8	LS601	3.00D	457	114	21	1255	965	1145	880	1060	815	960
16X6-8	LS603	4.33R	410	146	18	1545	1190	1410	1085	1305	1005	1185
18X7-8	LS601	4.33R	457	145	20	2430	1870	2215	1705	2060	1585	1870
18x7-8	LS605	4.33R	457	162	25	2430	1870	2215	1705	2060	1585	1870
6.00-9	LS601	4.00E	528	140	24	1975	1520	1805	1390	1675	1290	1520
21x8-9	LS605	6.00E	535	202	30	2890	2225	2645	2035	2455	1890	2230
6.50-10	LS601	5.00F	580	156	22	2715	2090	2485	1910	2310	1775	2090
23X9-10	LS603	6.50F	588	206	24	3730	2870	3405	2620	3160	2430	2865
200/50-10	LS604	6.50F	456	196	15	2910	2240	2665	2050	2470	1900	2240
23X10-12	LS604	8.00G	588	232	20	4450	3425	4060	3125	3770	2900	3420
7.00-12	LS601	5.00S	663	168	25	3105	2390	2835	2180	2635	2025	2095
28X9-15 (8.15-15)	LS601	7.0	706	215	27	4060	3125	3710	2855	3445	2650	3125
8.25-15	LS601	6.5	817	205	32	5085	3910	4640	3570	4310	3315	3910